

SOUTHWESTERN REGION 03 PRESCOTT NATIONAL FOREST

FOREST-WIDE WELL AND SEPTIC TANK DECOMMISSIONING

STATEMENT OF WORK



U.S. FOREST SERVICE
06/18/2026

responsible for the theft and/or vandalism of any materials or equipment left at the project site.

1.7 GOVERNMENT FURNISHED ITEMS AND MATERIALS

The Government will furnish the following:

- Road grading for Wilhoit Well Shaft location, NFSR 72 and 9402M
- ADWR Form 55-38, Notice of Intention to Abandon Well, for all ADWR-qualified wells, and associated fees, with coordination and information as requested by the Government from the Contractor

1.8 SUBMITTALS

Upon Award and prior to the start of construction activities, the Contractor shall furnish submittals for the following items:

- Construction schedule
- Well driller qualifications, meeting ADWR/ADEQ requirements

The Contractor shall furnish submittals for the following items:

- ADWR Form 55-58, Well Abandonment Completion Report, for all ADWR-qualified wells
- Camera inspection report, Wilhoit Well Shaft
- Daily Reports with pictures of construction activities

1.9 CONSTRUCTION SCHEDULE

Submit a detailed schedule that includes, but is not limited to:

- A detailed breakdown of all project tasks, phases, and sub-phases
- Key milestones, including Notice to Proceed, substantial completion, and owner-defined checkpoints.
- Buffer/Float: Inclusion of reasonable buffers for weather, inspections, or unforeseen conditions.

1.10 ARCHEOLOGICAL SITES AND DISCOVERY

If previously undocumented cultural resources are encountered during ground-disturbing activities, all work must immediately cease within one hundred (100) feet until a USFS archaeologist has documented the discovery and evaluated its eligibility for the National Register of Historic Places (NRHP) in consultation with the Arizona State Historic Preservation Office (SHPO). Work must not resume in the area without authorization from the USFS. Secure the area and relocate work to another area of the project.

If the unanticipated discovery involves human remains and/or associated objects on USFS lands, all work must immediately cease within one hundred (100) feet of the discovery and the USFS must be notified immediately of the discovery. The area of the find must be clearly

3.0 WELL ABANDONMENT SPECIFICATIONS

A. GENERAL

a. SUMMARY

- i. This section includes requirements for the abandonment of water supply wells.

b. SECTION REQUIREMENTS

- i. Submittals:
 - 1. Driller Qualifications (SD-07, Certificates), FIO
 - 2. DWR 55-58 (SD-07, Certificates), FIO
- ii. Forms: Verify with the required reporting agency to obtain the latest revised forms.
 - 1. DWR 55-58 Well Abandonment Completion Report

c. QUALIFICATIONS

- i. Submit personnel documentation and experience, including driller license with the State of Arizona, and document a minimum of 5 years of well installation and abandonment experience.

d. POLICY AND REGULATION

- i. Specifications herein are identified from the ADWR Well Abandonment Handbook, September 2008. Verify with the handbook all requirements prior to abandonment activities.

B. PRODUCTS

a. GENERAL

- i. Provide and install compatible materials for casing, screen, and other well material, to prevent galvanic reaction between components of the completed well.

b. MATERIALS

- i. Neat Cement Grout: Mixing ratio of one 94-pound sack of cement with not more than six (6) gallons of water, and pumped with a tremie pipe.
- ii. Concrete or Concrete Grout: Mixing ratio of cement, sand, and aggregate with no less than seven (7) 94-pound sacks of cement per cubic yard of